


ORDERING CODE 订购代码

HLS-14F1 D - DC12V - C



CONTACT FORM
C:1 FORM C A:1 FORM A
NOMINAL VOLTAGE
DC3V,DC5V,DC6V,DC9V,DC12V,DC24V,DC48V
COIL
D...STANDARD| 0.72W|
L...HIGH SENSITIVE| 0.53W|
TYPE

CONTACT DATA 触点参数:

Contact Form	触点形式	1A /1C	
Contact Material	触点材料	Ag Alloy	
Contact Ratings	触点负载	10A240VAC/10A 30VDC	
Max Switching Voltage	最大转换电压	250VAC/110VDC	
Max Switching Current	最大转换电流	10A	
Max Switching Power	最大转换功率	2500VA/300W	
Initial Contact Resistance	接触电阻(首次)	100m Ω Max	at6VDC 1A
Life Expectancy Electrical	电气寿命	100,000	Operations (rated load)
Life Expectancy Mechanical	机械寿命	10,000,000	Operations (no load)

GENERAL DATA 一般参数:


Insulation Resistance	绝缘阻值	1000M Ω Min at500VDC	
Dielectric Strength Between Open Contacts	触点间耐压	1000VAC 50-60HZ (1 minute)	
Dielectric Strength Between Contacts And Coil	触点与线圈间耐压	5000VAC 50-60HZ (1 minute)	
Operate Time	吸合时间	15ms max	
Release Time	释放时间	8ms max	
Ambient Temperature	环境温度	-30°C to +70°C	
Shock Resistance 冲击	Malfunction	动作极限	10G
	Destruction	破坏极限	100G
Vibration Resistance	振动	10-55Hz, 1.5mm double amplitude	
Ambient humidity	湿度	20-85% RH	
Weight	重量	Approx 13g	
Safety Standard	安全标准	TUV CE CQC	

COIL DATA 线圈参数: (@20°C)


Rated Voltage 额定电压 (VDC)	Coil Resistance Ω (±10%) 线圈阻值		Max Operate Voltage 最大吸合电压 (VDC)	Min Release Voltage 最小释放电压 (VDC)	Max Applied Voltage 最大允许电压 (VDC)
	0.53W	0.72W			
3	17	12.5	2.4	0.15	3.9
5	50	36	4	0.25	6.5

6	68	50	4.8	0.3	7.8
9	155	115	7.2	0.45	11.7
12	270	200	9.6	0.6	15.6
24	1100	820	19.2	1.2	31.2
48	4400	3300	38.4	2.4	62.4


Outline Dimension 外形尺寸(mm)




PC Board layout 安装图



Wiring Diagram 接线图



(Bottom View)底视



(Bottom View)底视