

Model: Power-Xtra PX18650-22E - 3.7V 2200 Mah Li-ion Battery- 5C
Stock Code: 900.600.503.321

TECHNICAL INFORMATIONS

Item	Specifications	Conditions
Nominal Voltage	3.7±0.05V	0.2C Discharge
Charging	Method	CC-CV
	Voltage	4.20±0.05V
Typ. Capacity	2.200 mAh	0.2C discharge
Standard Charge Current	1.100 mAh (0.5C)	Constant current at 1100mA charge to 4.20V, then constant voltage at 4.20V charge till current decline to ≤22mA
Standard Discharging Current	440 mAh (0.2C)	440mA to 2.75V
Max. Discharge Current	2.200 mAh (1.0C)	1.0C / 2200 mAh to 2.75V
Maximum Discharge Current	11.000 mAh (5.0C)	5.0C
Temperature	Charge	0 to +45°C
	Discharge	-20 to +60°C
	Storage	Less than 1 year: -20~25°C less than 3 months: -20~40°C
Weight	45 gr	approximately
Cycles Test	<p>During this cycle life test, the ambient temperature should be kept at 23°C ±2°C. The cell shall be charged at CC/CV=0.5C/4.20V, cut off till current decline to 0.05C, stored for 10mins, then discharged at a constant current of 0.5C to a final voltage of 2.75V, after that, stored 10mins prior to next charge/ discharge cycle.</p> <p>The cell shall be continuously charged and discharged for 300 times.</p>	

IMAGE

Technical Drawing

Diameter	18.7 mm
Height	65.5 mm



Image



REV002
 Revised Date:27.11.2020